



### Standard Features

- IP67 aluminum environmentally sealed load cell
- 304 stainless steel construction
- Meets HACCP requirements
- Five-point overload protection
- Specially designed adjustable support feet provide exceptional traction and will not scratch surfaces

### Specifications

#### Load Cell, NTEP Certified:

IP67 aluminum and environmentally sealed

#### Output Impedance:

350 ohm

#### Maximum Overload:

180% to 200% depending on capacity

#### Overload Protection:

Five-point, independently adjusted

#### Scale Frame:

AISI304L, straight line finish, Ra=45 +/- 10

#### Scale Cover:

AISI304L, straight line finish, Ra=45 +/- 10

#### Cable Length:

34 in or 10 ft

#### Compensated Temperature Range:

14 °F to 104 °F (-10 °C to 40 °C)

#### Warranty:

Two-year limited

#### Approvals:

NTEP CC 95-072, Class III 5,000 d  
Measurement Canada AM-5082  
Load cell is cFMus approved  
NSF approved

### Approvals



### Part Number/Price

Part #		Platform Capacity	Dimensions (L × W × H)	Est. Weight	Price
10 ft cable	34 in cable				
112599	106137	5 lb (2.5 kg)	10 × 10 × 4.25 in	14 lb	Consult
112601	106138	10 lb (5 kg)	10 × 10 × 4.25 in	14 lb	Consult
112603	106139	25 lb (10 kg)	10 × 10 × 4.25 in	14 lb	Consult
112605	106140	25 lb (10 kg)	12 × 12 × 4.25 in	17 lb	Consult
112607	106141	50 lb (25 kg)	12 × 12 × 4.25 in	17 lb	Consult
112609	106142	100 lb (50 kg)	12 × 12 × 4.25 in	17 lb	Consult

### Options/Accessories

Part #	Description	Catalog Page #
Consult	Scale columns	See page 201
Consult	Ball transfer and roller conveyor scale tops	See page 200
Consult	Mobile scale carts	See page 196 to page 199

#### Dimensions

##### 10 × 10 in

A	4.25 in	C	10.00 in
B	10.00 in	C1	10.25 in
B1	10.25 in		

Note: 1 in = 25.4 mm

#### Dimensions

##### 12 × 12 in

A	4.25 in	C	12.00 in
B	12.00 in	C1	12.25 in
B1	12.25 in		

Note: 1 in = 25.4 mm

